

WALL MOUNTED COMBINATION BOILER



- SEDBUK Band D
- Top flue outlet with optional rear flue exit within case
- 24kW and 28kW models available giving flow rates of 9.7 lts/min and 11.5 lts/min (at 35°C temperature rise)
- Patented 'bi-thermic' heat exchanger providing rapid delivery of domestic hot water
- Fully modulating burner which accurately matches output to demand
- Versatile concentric and twin flue options available
- Compact dimensions - only 740mm (H) x 400mm or 450mm (W) x 328mm (D)
- Built-in 24-hour time clock
- Many built-in features:
 - Frost protection
 - Anti-cycling control
 - Automatic by-pass
 - Electronic ignition
 - Full flame modulation
 - Automatic pump spin
- Backed up by Vokèra's industry leading service and technical support

Vokèra Ltd.
4th Floor,
Catherine House,
Boundary Way,
Hemel Hempstead. HP2 7RP
Tel: 0870 3330520
Fax: 01442 281460

	Units	Compact 24	Compact 28
Heat Output	kW	24.0	28.0
DHW Flow Rate (35°C Rise)	Lt/min	9.7	11.5
SEDBUK Efficiency	%	78.4	78.0
Maximum Flue Length			
Horizontal (Ø100mm)	m	4.5	3.4
Vertical (Ø100mm)	m	5.25	4.4
Twin (Ø80mm)	m	14/14*	14/14*
Height (ex. flue elbow)	mm	740	740
Width	mm	400	450
Depth	mm	328	328
Connections			
Flow and Return	mm	22	
Cold Water and DHW	mm	15	
Safety Valve	mm	15	
Gas	mm	15	

* plus flue terminal