

## HIGH EFFICIENCY CONDENSING COMBINATION BOILER



- SEDBUK Band A
- 26kW heat output with full air/gas modulation to accurately match output to demand
- Pre-mix combustion minimises emissions of harmful greenhouse gases - NO<sub>x</sub> and CO<sub>2</sub>
- Easy to use digital control panel provides accurate control of temperatures
- Simple installation and commissioning
- Stylish casing allows siting of boiler in prominent positions
  - Many built-in features:
    - Anti-cycling control
    - Filling loop
    - Frost protection
    - Automatic by-pass
    - Self diagnostic fault finding
    - Automatic pump spin
- Versatile concentric and twin flue options available
- Optional weather compensating control which automatically adjusts boiler operating parameters to suit outside weather conditions
- Backed up by Vokera's industry leading service and technical support

	Units	Hydra
Heat Output - CH (80°/60°)	kW	25.3
- CH (50°/30°)	kW	26.8
- DHW	kW	25.3
DHW Flow Rate (35°C Rise)	Lt/min	10.4
SEDBUK Efficiency	%	90.3
Maximum Flue Length		
Horizontal (Ø100mm)	m	6.45
Vertical (Ø100mm)	m	7.45
Twin (Ø80mm)	m	29/29*
Height (ex. flue elbow)	mm	820
Width	mm	450
Depth	mm	355
Connections		
Flow and Return	mm	22
Cold Water and DHW	mm	15
Safety Valve	mm	15
Gas	mm	15
Condensate	mm	21.5

\* plus flue terminal

Vokera Ltd.  
 4th Floor,  
 Catherine House,  
 Boundary Way,  
 Hemel Hempstead. HP2 7RP  
 Tel: 0870 3330520  
 Fax: 01442 281460